

Neu!
Schnelllauf-Motoren
bis zu 60 U/min!



OZRoll DC motors

For blinds and shutters, awnings, furniture, automotive industry and more



- Tubular motors from 10 to 35 Nm with mechanical endstop
- High duty cycle for frequent and long term operation
- solid, well-proven quality
- Adaptors for all common axle types available
- wide range of accessories on stock
- Lateral motor for narrow shutters and other applications
- Venetian blind motor Q6 with electronic endstop setting
- Operation with OZRoll Solar Pro, E-Port or ACCUFIX
- Alternative operation with user-specific control systems
- High speed tubular motors up to 60 rpm

Tubular Motor T10, 12V 10Nm

Length: 556 mm
 Tube diameter: 35 mm
 Current: 12 V DC
 Torque: ca. 10 Nm
 IP class: Ip44
 Operating temp.: -20°C/+60°C
 Consumption: max. 2,8 A
 Speed: 16 rpm



Tubular Motor T20, 12V 20Nm

Length: 587 mm
 Tube diameter: 45 mm
 Current: 12 V DC
 Torque: approx. 20 Nm
 IP class: Ip44
 Operating temp.: -20°C/+60°C
 Consumption: max. 2,8 A
 Speed: 16 rpm



Tubular Motor T35, 12V 35Nm

Length: 587 mm
 Tube diameter: 45 mm
 Current: 12 V DC
 Torque: approx. 35 Nm
 IP class: Ip44
 Operating temp.: -20°C/+60°C
 Consumption: max. 2,8 A
 Speed: 12 rpm



Venetian-Blind-Motor Q6

Torque: 2 x 3 Nm
 Current: 12 V
 Operating temperature: -5°C/+50°C
 Speed: approx 20 rpm
 Consumption: approx. 3A
 IP-class: Ip54
 Total length: 260 mm



Lateral Motor L10

Torque: 10 Nm
 Tension: 12 V
 Operating temp.: -20°C/+60°C
 Geschwindigkeit: approx. 16rpm
 Consumption: approx. 3,6A
 IP protection class: Ip44

